

JF 丁腈聚氯乙烯复合物绝缘电机绕组引接电缆（电线）

JF JBF insulation motor leader wire and cable

● PRODUCT DESCRIPTION

- Rated temperature: 70°C
- Rated voltage: 500V
- According to standard : QB/ZL080313-2008
- Stranded, tinned or bare cooper conductor
- JBF insulation
- For used leads wiring of E, B Insulation class motor

● 产品说明

- 额定温度: 70°C
- 额定电压: 500v
- 执行标准: QB/ZL080313-2008
- 导体使用绞合镀锡丝或裸铜丝
- 丁腈 PVC 绝缘料
- 用于 E、B 级电机引出线

NOM.AREA OF COND 标称截面	COMPOSITION OF COND 导体结构	THICKNESS INSULATION 绝缘标称厚度	MAX.O.D 最大外径上限	MAX.COND.RESISTANCE (20°C) 最大导体电阻(20°C) Ω/km	
				镀锡铜芯	铜芯
mm ²	No/mm	mm	mm		
0.12	6/0.16	0.6	2.1	163	158
0.2	10/0.16	0.6	2.3	95.0	92.3
0.3	15/0.16	0.6	2.4	71.2	69.2
0.4	19/0.16	0.6	2.5	49.6	82.2
0.5	16/0.20	0.6	2.6	40.1	39.0
0.75	24/0.20	0.6	2.8	26.7	26.0
1.0	32/0.20	0.6	3.0	20.0	19.5
1.5	30/0.25	0.6	3.3	13.7	13.3
2.5	49/0.25	0.7	3.9	8.21	7.98
4	56/0.30	0.8	4.7	5.09	4.95
6	84/0.30	1.0	6.2	3.39	3.30
10	84/0.40	1.2	7.8	1.95	1.91
16	126/0.40	1.2	9.0	1.24	1.21
25	196/0.40	1.4	11.5	0.795	0.78
35	276/0.40	1.4	12.7	0.565	0.554
50	396/0.40	1.6	14.7	0.393	0.386