

JYJ150 150℃辐照交联阻燃聚烯烃绝缘电机绕组引接线
 JYJ150 150℃Radiation across-linked XLPE insulation

● PRODUCT DESCRIPTION

- Rated temperature: 150℃
- Rated voltage: 500V
- According to standard : QB/ZL080305-2008
- Stranded, tinned or bare cooper conductor
- Radiation across-linked Low-smoke, non-halogen, flame-retardant XLPE insulation
- For used leads wiring of B, F, H Insulation class motor

● 产品说明

- 额定温度: 150℃
- 额定电压:500v
- 执行标准: QB/ZL080305-2008
- 导体使用绞合镀锡丝或裸铜丝
- 辐照交联低烟无卤阻燃聚烯烃绝缘
- 用于 B、F、H 电机引出线

NOM.AREA OF COND 标称截面	COMPOSI TION OF COND 导体结构	FINSHED PRODUCT 成品		CURRENT RATING OF ELECTRIC(25℃) 25℃时空气敷设 载流量	MAX.COND.RESIST ANCE (20℃) 最大导体电阻(20℃) Ω/km	
		THICKNESS INSULATION 绝缘标称厚度	MAX.O.D 最大外径上限		镀锡铜芯	铜芯
mm ²	no/mm	mm	mm	A		
0.5	16/0.20	0.8	3.3	15	40.100	39
0.75	24/0.20	0.8	3.5	17	26.700	26
1.0	32/0.20	0.8	3.7	19	20.000	19.5
1.5	30/0.25	0.8	4.0	24	13.700	13.3
2.5	49/0.25	0.8	4.4	33	8.210	7.98
4.0	56/0.30	0.8	5.0	45	5.090	4.95
6.0	84/0.30	1.2	6.1	58	3.390	3.30
10	84/0.40	1.2	7.9	80	1.950	1.91
16	126/0.40	1.2	9.0	107	1.240	1.21
25	196/0.40	1.2	10.8	138	0.795	0.78
35	276/0.40	1.2	12.0	171	0.565	0.554
50	396/0.40	1.4	14.2	210	0.393	0.386
70	360/0.50	1.6	16.8	269	0.277	0.272
95	475/0.50	1.6	18.9	328	0.210	0.206
120	608/0.5	1.6	21.1	415	0.164	0.161